

# 4K / HD Integrated Camera Output Format/ Function Comparison

	4K Integrated Camera	HD Integrated camera			Full-HD Outdoor Integrated Camera
Model No.	AW-UE70W/K AW-UN70W/K	AW-HE130W/K AW-HN130W/K	AW-HE40 series AW-HN40HW/HK	AW-HE38HW/HK AW-HN38HW/HK	AW-HR140
<b>Output Signal Format</b>					
2160/29.97p, 25p	✓ HDMI output only	—	—	—	—
1080/59.94p	✓	✓	✓ HDMI model only	✓	✓
1080/29.97p	✓	✓ <sup>*1</sup>	✓	✓	✓ <sup>*1</sup>
1080/23.98p	—	✓ <sup>*2</sup>	—	—	✓ <sup>*2</sup>
1080/50p	✓	✓	✓ HDMI model only	✓	✓
1080/25p	✓	✓ <sup>*1</sup>	✓	✓	✓ <sup>*1</sup>
1080/59.94i	✓	✓	✓	✓	✓
1080/50i	✓	✓	✓	✓	✓
1080/29.97PsF	✓	✓ <sup>*3</sup>	✓	✓	✓ <sup>*3</sup>
1080/25PsF	✓	✓ <sup>*3</sup>	✓	✓	✓ <sup>*3</sup>
1080/23.98PsF	—	✓ <sup>*3</sup>	—	—	✓ <sup>*3</sup>
720/59.94p	✓	✓	✓	✓	✓
720/50p	✓	✓	✓	✓	✓
576/50p	—	✓ <sup>*4</sup>	—	—	—
576/50i	—	✓ <sup>*4</sup>	—	—	—
480/59.94p	—	✓ <sup>*4</sup>	—	—	—
480/59.94i	—	✓ <sup>*4</sup>	—	—	—
<b>Function</b>					
CineGamma	✓	✓	✓	✓	✓
DRS	✓	✓	✓	✓	✓
Hybrid DNR	—	✓	—	—	✓
HDR mode	✓ (Combine Images)	—	✓ (Combine Images)	✓ (Combine Images)	—
Optical Image Stabilization (OIS)	✓	✓	—	—	✓
Dynamic Image Stabilizing System (D.I.S.S.)	—	—	—	—	✓
Digital Image Stabilization	✓	—	✓	✓	—
Digital Extender Zoom	✓	✓	✓	✓	✓
i.Zoom	✓	—	✓	✓	—
Independent Color Correction Function	16-axis Color	12-axis Color 3-axis Skin Tone	16-axis Color	16-axis Color	12-axis Color 3-axis Skin Tone
Color Temperature Adjustment Mode	✓	✓	✓	✓	✓
Scene files	4 files	4 files	4 files	4 files	4 files
Freeze During Preset function	✓	✓	✓	✓	✓
Night mode	✓	✓	✓	✓	✓
IP control	✓	✓	✓	✓	✓
IP video monitoring	✓	✓	✓	✓	✓
HD video output via IP transmission	H.264	4K/Full HD	Full HD	Full HD	Full HD
	Motion JPEG	4K*/Full HD	Full HD	Full HD	Full HD
PoE	PoE+	PoE+	PoE+	PoE+	PoE++ <sup>*6</sup>
Wireless Remote Control	Up to 4	Up to 4	Up to 4	Up to 4	—
Turn-lock mechanism	✓	✓	✓	✓	—
Fan-less design	✓	✓	✓	✓	—
Color variations	black/white	black/white	black/white	black/white	silver
USB Video Class 1.0	✓	—	✓	✓	—
Audio Input	✓	✓	✓	✓	✓

\*1: Native output \*2: Over 59.94i \*3: For 1080/25PsF, there are cases where 50i is displayed on the monitor. \*4: A 'P' signal is output as HDMI output, an 'I' signal is output as SDI and an analog output for output formats of 480/59.94p(i) and 576/50p(i). \*5: USB only. \*6: Conforms to IEEE802.3bt (Draft ver. 2.0).